

Appl. No. 10/064,983

Response dated December 3, 2003

Reply to Notice of Non-Complaint Amendment dated November 18, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims

1. (previously presented) A method for forming an OLED device comprising:
forming a device layer on a substrate having an active region defined thereon in which pixels are formed;
patterning the device layer to form pillars along a first direction on the substrate, wherein the pillars comprise a tapered profile, and grooves between the pillars, the pillars extend outside the active region to prevent electrical shorting;
coating the substrate with a solution comprising an organic functional material dissolved in a solvent, the pillars are inert to the solvent;
removing the solvent to form an organic functional layer; and
depositing a conductive layer in the electrode region on the substrate, wherein the tapered profile of the pillars separate the conductive layer into first and second distinct portions.
2. (original) The method of claim 1 wherein a distance D is provided between the edge of the active region and ends of the grooves.
3. (original) The method of claim 2 wherein D is at least 300µm.
4. (original) The method of claim 2 further comprises mounting a cap on the substrate to hermetically seal the OLED device.
5. (original) The method of claim 4 wherein the substrate comprises a flexible substrate.
6. (original) The method of claim 5 wherein the substrate comprises electrodes in a second direction on a surface thereof.

Appl. No. 10/064,983

Response dated December 3, 2003

Reply to Notice of Non-Complaint Amendment dated November 18, 2003

7. (original) The method of claim 6 wherein the functional organic material comprises a conjugated polymer dissolved in a solvent.

8. (original) The method of claim 1 wherein the device layer comprises a photosensitive device layer, the photosensitive layer is patterned by exposing and developing the photosensitive device layer.

9. (original) The method of claim 8 wherein the photosensitive layer comprises a positive photosensitive layer, wherein exposed portions of the photosensitive layer are removed during developing.

10. (original) The method of claim 9 wherein exposing comprises successively exposing the photosensitive layer with electrons or charged particles having different energies which have different penetration depths to form pillars with the tapered profile during developing.

11. (original) The method of claim 8 comprises curing the pillars to render the pillars inert against the solvent.

12. (previously presented) A method for forming an OLED device comprising:
forming a device layer on a substrate having an active region defined thereon in which pixels are formed;

 patterning the device layer to form pillars along a first direction on the substrate, wherein the pillars comprise a tapered profile, and grooves between the pillars, the pillars extend outside the active region to edges of the substrate to prevent electrical shorting;

 coating the substrate with a solution comprising an organic functional material dissolved in a solvent, the pillars are inert to the solvent;

 removing the solvent to form an organic functional layer; and

 depositing a conductive layer on the substrate, wherein the tapered profile of the pillars separate the conductive layer into first and second distinct portions.

Appl. No. 10/064,983

Response dated December 3, 2003

Reply to Notice of Non-Complaint Amendment dated November 18, 2003

13. (original) The method of claim 12 further comprises mounting a cap on the substrate to hermetically seal the OLED device.
14. (original) The method of claim 12 wherein the substrate comprises a flexible substrate.
15. (original) The method of claim 12 wherein the substrate comprises electrodes in a second direction on a surface thereof.
16. (original) The method of claim 15 wherein the functional organic material comprises a conjugated polymer dissolved in a solvent.
17. (original) The method of claim 16 wherein the device layer comprises a photosensitive device layer, the photosensitive layer is patterned by exposing and developing the photosensitive device layer.
18. (original) The method of claim 17 wherein the photosensitive layer comprises a positive photosensitive layer, wherein exposed portions of the photosensitive layer are removed during developing.
19. (original) The method of claim 17 wherein exposing comprises successively exposing the photosensitive layer with electrons or charged particles having different energies which have different penetration depths to form pillars with the tapered profile during developing.
20. (original) The method of claim 19 comprises curing the pillars to render the pillars inert against the solvent.
21. (previously presented) A method for forming an OLED device comprising:
forming a device layer on a substrate having an active region defined thereon in which pixels are formed;

Appl. No. 10/064,983

Response dated December 3, 2003

Reply to Notice of Non-Complaint Amendment dated November 18, 2003

 patterning the device layer to form pillars along a first direction on the substrate, wherein the pillars comprise a tapered profile and grooves between the pillars, the pillars extend outside the active region to prevent electrical shorting;

 forming an organic functional material on the substrate; and

 depositing a conductive layer in the electrode region on the substrate, wherein the tapered profile of the pillars separate the conductive layer into first and second distinct portions.

22. (previously presented) The method of claim 21 wherein grooves extend outside the active region to the edges of the substrate.

23. (previously presented) The method of claim 22 wherein forming an organic functional material on the substrate comprises coating the substrate a solution comprising the organic functional material dissolved in a solvent and wherein the pillars are inert to the solvent.

24. (previously presented) The method of claim 22 wherein:
 the device layer comprises a photosensitive material; and
 the device layer after the pillars are formed is cured to render the pillars inert to the solvent.

25. (previously presented) The method of claim 21 wherein forming an organic functional material on the substrate comprises coating the substrate a solution comprising the organic functional material dissolved in a solvent and wherein the pillars are inert to the solvent.

26. (previously presented) The method of claim 25 wherein:
 the device layer comprises a photosensitive material; and
 the device layer after the pillars are formed is cured to render the pillars inert to the solvent.

Appl. No. 10/064,983

Response dated December 3, 2003

Reply to Notice of Non-Complaint Amendment dated November 18, 2003

27. (previously presented) The method of claim 21 wherein:
the device layer comprises a photosensitive material; and
the device layer after the pillars are formed is cured to render the pillars inert to the solvent.
28. (withdrawn) An OLED device comprising:
a substrate having an active region defined thereon, the active region comprises pixels; and
pillars along a first direction on a substrate, wherein the pillars comprise a tapered profile and grooves between the pillars, the pillars extend outside an active region of the substrate to prevent electrical shorting.
29. (withdrawn) The OLED device of claim 28 wherein:
the pixels comprise an organic functional layer formed by depositing a solution having organic function material dissolved in a solvent; and
the pillars are inert to the solvent.
30. (withdrawn) The OLED device of claim 29 wherein the pillars comprises a photosensitive material, the pillars are cured to render the pillars inert to the solvent.
31. (withdrawn) The OLED device of claim 29 wherein the pillars extend outside the active region to the edges of the substrate.
32. (withdrawn) The OLED device of claim 28 wherein the pillars comprises a photosensitive material, the pillars are cured to render the pillars inert to the solvent.
33. (withdrawn) The OLED device of claim 32 wherein the pillars extend outside the active region to the edges of the substrate.
34. (withdrawn) The OLED device of claim 28 wherein the pillars extend outside the active region to the edges of the substrate.

Appl. No. 10/064,983

Response dated December 3, 2003

Reply to Notice of Non-Complaint Amendment dated November 18, 2003


Conclusion

In view of the foregoing, Applicants believe that all claims now pending in this application are in condition for allowance. The issuance of a formal Notice of Allowance at an early date is respectfully requested. It is believed that no fees are due associated with the filing of this response. The Commissioner, however, is authorized to charge any fees or credit any overpayment to Deposit Account No. 50-2388.

Should the Examiner believe that a telephone conference would expedite prosecution of this application, please telephone the undersigned attorney at his number set out below.

Date: December 3, 2003

Respectfully submitted,



Dexter CHIN
Attorney for Applicants
Reg. No. 38,842

Horizon IP Pte Ltd
166 Kallang Way
6th Floor
Singapore 349249
Tel: (65) 9836 9908
Fax: (65) 6746 8263